



ADDRESS
PRINTING

TABBING
SOLUTIONS

MAILING
SOFTWARE



DIGITAL COLOR
PRINTING

SUPPLIES CONTACT

ENVELOPE IMAGER 1.5 PLUS



Key Features

- 30,000 Postcards/hr
- 1.5" of Print From One Print Module
- 3/16" Thickness Capability
- Clutch-Control Integrated Feeder
- Extended Material Hopper
- High Speed USB 2.0 Port



Many improvements adorn the Envelope Imager 1.5 Plus. This formidable little machine can churn out some serious productivity. Offering all of the same features as the entry-level 1.5, the Plus has an extended hopper that can hold a whole box of #10 envelopes (500) at a time. It can also take materials up to a class-leading 3/16" thick. The sleek control panel and professional grade color scheme lets you know that this printer means business.

[View Brochure](#) | [View Video](#) | [Dealer Locator](#)

Print Technology	Thermal Inkjet, Three HP 45A-Style High Capacity Cartridges		
Address Speed	30,000 /hour at 150 dpi 25,000 /hour at 200 dpi 20,000 /hour at 300 dpi 11,500 /hour at 600 dpi (9 Lines on 4"x6" Postcard)		22,000 /hour at 150 dpi 19,000 /hour at 200 dpi 15,000 /hour at 300 dpi 7,200 /hour at 600 dpi (9 Lines on #10 Envelopes)
Print Quality (Dots Per Inch)	Description	Dots Per Inch	Resolution
	High Quality	600 d.p.i.	600 x 600 dpi
	Letter Quality	300 d.p.i.	600 x 300 dpi
	Standard Quality	200 d.p.i.	600 x 200 dpi
	Hi-Speed Quality	150 d.p.i.	600 x 150 dpi
Image Area	1.5" X 14" w/ 9.5" Vertical Range		
Print Head Split	3 Pen Stitched Design		
Processor	AMD TigerSharc 100 MHz DSP with Dual Calculation Technology		
Memory	64 MB RAM		
Fonts	All TrueType fonts available on PC		
Print Orientation	Normal and Reverse		
	One operator resettable job counter, one permanent		

Counters	lifetime counter
Ink Monitor	Visible on Display
Prints	Allows printing of graphics, logos, and barcodes
Material Size	Minimum (W x L): 3" x 5" Maximum (W x L): 14" x 14"
Material Thickness	Up to 3/16"
Feeder-Capacity	Up to 500 #10 Envelopes
Software	Windows™ Printer Drivers for Windows™ 98, 2000, NT, ME, and XP
PC Interface	Parallel and USB 2.0
Diagnostics	Resident in firmware
Firmware Update	Flash PROM update.
Duty Cycle	30 million addresses total or 500,000 per month over a 5-year life cycle.
Dimensions	19" H x 21" L x 20.5" W
Weight	53 lbs
Electrical	115VAC or 240VAC 50/60 Hz
Options	RENA Systems EASYInks, HP Versatile fast dry Black, and Spot Colors, Conveyor/Stacker/Dryer, Drop Tray

[OUR STORY](#) | [SUPPORT](#) | [DRIVERS](#) | [GLOSSARY](#)

RENA SYSTEMS, INC IS DEDICATED TO THE DESIGN AND MANUFACTURE OF THE WORLD'S FINEST MAILING PRODUCTS.
WHEN QUALITY IS THE FIRST ITEM ON YOUR LIST, RENA SYSTEMS IS THE ONLY NAME TO CONSIDER.

910 East Main Street
Suite 200, Norristown, PA
19401-4110

Telephone: (610) 650-9170
Toll Free: (888) 444-RENA

Fax: (610) 270-3947
E-mail: sales@renausa.com



COPYRIGHT © 2015 RENA Systems, Inc., a Neopost brand. [Privacy Policy](#)
Website and CMS by [Navitas Marketing](#) and [Global Media Solutions](#)