



T-750 IN-LINE TABBER



T-750 IN-LINE TABBER

	SPEED	
	SINGLE TAB	Up to 20,000 pieces per hour
	DOUBLE TAB	
	TRIPLE TAB	Up to 8,000 pieces per hour (11" min. piece length)
	MATERIAL SIZE	MINIMUM: 3" x 5" – MAXIMUM: 13" x 17"
	MATERIAL THICKNESS	Up to 3/8"
	TAB SIZE	MINIMUM: 3/4" x 3/4" – MAXIMUM: 1-1/2" x 1-1/2"
	REEL CAPACITY	Up to 14" – 3" core
	NUMBER OF TABS	1, 2, or 3
	TAB ACCURACY	+/- 1/16"
	FEEDER	In-line design works with various input devices
	FEEDER CONTROL	Synchronized Speed Control with EASYFeed Lite
		Start/Stop Control for other feed systems
-	PRODUCTION COUNTERS AND DISPLAYS	Life and Job Count and Production rate and speed
	ERROR REPORTING	YES
	FEATURES	Optional Synchronized Feeder (EASYFeed Lite) - Can apply up to three stamps
	SAFETY	Emergency Stop button & Interlocks on all adjustments
-	DIMENSIONS	25" W x 27" H (with reel) x 41" L (with feeder)
	WEIGHT	90 lbs. (40.9 kg)
	ELECTRICAL	115VAC 50/60Hz
100	OPTIONS	RENA Systems EASYFeed Feeders, Conveyor/Stackers and Tabs
-	DUTY CYCLE	60 million addresses total or 1,000,000 per month over a 5-year life cycle





You need to produce inexpensive non-enveloped mass mailings and brochures that look great and meet postal discount requirements with a tight secured seal on every piece.

The versatile RENA Systems T-750 In-Line Tabber/Stamp Affixer produces high speed, high production and high quality tabbing or stamp affixing at a very affordable cost. Kick it up a notch in quality with precision feeding and accurate tab application all at production speeds, up to 20,000 pieces per hour. The T-750 will automatically apply translucent or paper wafer seals to a wide variety of open-ended media including mail pieces, folded stock, double postcards, newsletters, booklets, etc., up to 3/8" thick. The tabbing is accurate to within 1/16 of an inch. RENA

Systems technology gives you the control to adjust speed and placement, and choose from a variety of programming options. You can apply one, two or three tabs in a single pass.

The Tabbing system is designed to run in-line with various feeding/printing devices. It offers synchronized speed control with the EASYFeed Lite and Start/Stop Control with other RENA Systems feeders. An emergency stop button and interlocks on all adjustments give you state-of-the-art safety.

The T-750 is easy-to-set up, easy-to-run and is built with heavy-duty aluminum and steel construction to give you years of reliable, high performance use.

KEY FEATURES

- Production speeds up to 20,000 pieces/hr., double tab at 12,000 pieces/hr., triple tab at to 8,000 pieces/hr.
- Use paper, translucent or clear tabs on rolls up to 14" in diameter (up to 30,000 tabs)
- Applies tabs, small labels or USPS stamps one, two or three at a time
- Automatic tab detection and positioning

AUTHORIZED RENA SYSTEMS DEALER:



136 Green Tree Road PO Box 1069 Oaks, PA 19456-1069 Toll Free: 888.444.7362

